



Adresa: AG FOIL s r.o., 922 08 Veselé 426
Účet: CSOB Piešťany 4001287531/7500
IČO / IČ DPH: 35823801 / SK2021598920
Tel: +421 33 77 205 41, 77 205 42
Fax: +421 33 77 205 43
e-mail: predaj@agfoil.com
url: www.agfoil.com

Spoločnosť je registrovaná v OR OS Trnava vložka č. 14481/T.

Thermal Transfer Ribbon – Near Edge

|| AG71 NE ||

Description:

AG71 is the most used near-edge thermal transfer foil. The main characteristic of AG71 is maximum performance. It can be used with a wide variety label applications and tags. AG71 offers outstanding printing quality at high speed with good scratch and smear resistance. It is possible to choose from wide range already slitted rolls for different types of thermal transfer printers.

AG71 is suitable for printers with near-edge such as Avery, Novexx, Tec, Smardate and others.

Recommended media:

- coated and uncoated tag label stocks
- gloss and semi gloss labels
- polypropylene films
- polyethylene labels
- vinyl

Applications:

- general purpose labelling
- shipping, warehousing, and receiving labelling
- retail tag and label applications
- industrial and outdoor applications
- automotive applications
- pharmaceutical and healthcare applications
- flexible packing applications

Technical specifications:

Film Thickness	4,5 microns
Total ribbon thickness	7,0 microns
Transmition density	0,80 MacBeth Scale
Recommended maximum print speed	300mm/s
Ink melting temperature	70°C/158°F

* The information contained herein relates only to the specific material identified. The information is given according to our best knowledge and experience as of the date of this data sheet. No representation, guarantee or warranty, express or implied, is made as to the accuracy, reliability or completeness of this information. The receiver of this information is urgently requested to make his own determination as to the information's suitability and completeness for this particular application.